

400# Nitrile Covered Fire Hose - Light Duty Red

Application:

- ideal for industrial and construction washdown and discharge applications

Features:

- synthetic rubber compound formulated for flexibility and abrasion and chemical resistance
- ribbed for hose protection and easy handling
- outer construction: thin ribbed nitrile
- tube construction: nitrile
- proof pressure: **400 PSI** at ambient temperature (70°F)
- service test pressure: **200 PSI** at ambient temperature (70°F)
- working pressure: **180 PSI** at ambient temperature (70°F)

Uncoupled

Size	Bowl	Length	Part #	Price/E
2"	2¼"	50'	H420R50UC	\$545.30



Coupled with Female and Male NPSH brass rocker lug expansion ring couplings

Size	Length	Part #	Price/E
2"	50'	H420R50RBS	\$871.40



- other lengths, threads and couplings are available, contact Dixon™

500# Nitrile Covered Fire Hose - Light Duty Red

Application:

- ideal for industrial and construction washdown and discharge applications

Features:

- outer construction: thin ribbed nitrile
- tube construction: nitrile
- proof pressure: **500 PSI** at ambient temperature (70°F)
- service test pressure: **250 PSI** at ambient temperature (70°F)
- working pressure: **225 PSI** at ambient temperature (70°F)
- 25' lengths, other colors, threads and configurations are available, consult Dixon™

Uncoupled

Size	Bowl	Length	Part #	Price/E
1½"	1-13/16"	50'	H515R50UC	\$429.70
2½"	2-13/16"	50'	H525R50UC	663.00
1½"	1-13/16"	100'	H515R100UC	781.20
2½"	2-13/16"	100'	H525R100UC	1147.25



P

Coupled with female and male expansion ring couplings

Size	Length	Part #	Rocker Lug Aluminum NST (NH) RAF	Rocker Lug Brass NST (NH) RBF	Pin Lug Brass NST (NH) PBF	Rocker Lug Aluminum NPSH RAS
1½"	50'	H515R50	\$488.95	\$540.80	\$661.55	\$538.25
2½"	50'	H525R50	799.85	876.70	965.20	799.85
1½"	100'	H515R100	1016.65	---	---	1144.20
2½"	100'	H525R100	1386.00	---	---	1363.10



- other lengths, threads and couplings and other colors (yellow, red, blue and black) are available, contact Dixon™