

## PVC Braided Tubing

### Application

- For use with standard shank fittings in low-pressure liquid and pneumatic applications

### Domestic

### Features

- High grade tensile strength polyester yarn reinforcement
- Shipped in coils, sold only in lengths shown below

### Specification

- Temperature range: 27°F to 150°F (-3C to 66°C)

Size		Working Pressure PSI @ 72°F (22°C)	Length	Clear PVC Part #
O.D.	I.D.			
.625"	3/8"	265	300'	BR0609
.728"	1/2"	215	300'	BR0812
.906"	5/8"	200	300'	BR1014
1.024"	3/4"	150	300'	BR1218
1.732"	1-1/4"	110	100'	BR2027
1.950"	1-1/2"	90	100'	BR2431



### Imported

### Features

- For various machine tools and the transportation of chemicals
- Shipped in bundles wrapped with PVC film, sold only in lengths shown below

### Specification

- Temperature range: 14°F to 149°F (-10°C to 65°C)

Size		Working Pressure PSI @ 72°F (22°C)	Length	Clear PVC Part #
O.D.	I.D.			
1/2"	1/4"	142	300'	IBR0446
5/8"	3/8"	114	300'	IBR0609
3/4"	1/2"	100	300'	IBR0812
1-1/16"	3/4"	71	300'	IBR1218
1-5/16"	1"	71	200'	IBR1621



## D.O.T. Air Brake Tubing Rolls

### Feature

- Tubing cutters sold on page 1014

### Specifications

- Working pressure: 150 PSI
- Temperature range: -40°F to 200°F (-40°C to 93°C)

### Approval

- Meets Department of Transportation FMVSS-106 nylon material conforming to SAE J844

Tube Size	Tubing Color	Length	Nylon Part #
1/4"	black	100'	J844-04-BL-100
	blue	100'	J844-04-B-100
	red	100'	J844-04-R-100
3/8"	black	100'	J844-06-BL-100
	blue	100'	J844-06-B-100
	red	100'	J844-06-R-100
1/2"	black	100'	J844-08-BL-100
5/8"	black	100'	J844-10-BL-100
3/4"	black	100'	J844-12-BL-100



Q