



### Bumpered Fog Nozzles

**Features**

- Straight stream, capable of greater than 100° spray angle
- Twist shut-off and flow-type change

**Specification**

- Maximum working pressure: **100 PSI**; maximum rated pressure: **175 PSI**

**Approvals**

- FM Approved for class A and B fires
- UL certified for class A and B fires



BBN75

Size	Thread	Rated Flow at Rated Pressure (GPM)	Rated Flow at Wide Open: GPM @ 100 PSI	Approvals			Brass Part #
				FM	UL	ULC	
3/4"	GHT	54	54	✓	✓	✓	BBN75GHT
	NPSH			✓	✓	✓	BBN75
1"	NPSH	60	60	✓	✓	✓	BBN100
	NST			✓	✓	✓	BBN100NST



### Industrial Fog Nozzles

**Features**

- Delivers 30°-60°-90° fog pattern - shut-off - straight stream - fog
- Supplied with bumper

**Specification**

- Maximum operating pressure: **175 PSI** (water only) at 70°F (21°C)

**Approvals**

- UL listed and Factory Mutual approved for class A and B fires (except noted <sup>1,2</sup>)



BFN150



BFN200

Size	Thread	90° Spray GPM @ 100 PSI	Brass Part #
1-1/2"	NPSH	85	BFN150
2"		108	BFN200 <sup>1,2</sup>
2-1/2"		205	BFN250 <sup>2</sup>
1"	NST (NH)	32	BFN100NST
2-1/2"		205	BFN250NST <sup>2</sup>

<sup>1</sup> Not UL listed

<sup>2</sup> Not Factory Mutual approved

NOTE: Replacement washers can be found on page 780

N